



Arrivaa™ NC

Balloon Dilatation Catheter



Advanced Laser welding Technology to realize seamless connection between head and tube.

Tri-Fold Shape Memory Technology offers excellent rewarpability for multiple inflation uses.

Silicone Resin into The Guidewire Lumen to create a smooth, low-friction path for seamless guidewire movement through the catheter.

Arrivaa™ NC

Balloon Dilatation Catheter



TECHNICAL SPECIFICATIONS

Category:	Rapid Exchange Balloon Catheter	Category:	Non Complaint
Guiding Catheter Compatibility: 5F		Material	Polyamide
Guidewire Compatibility	0.014"	X-Ray visibility:	Two markers
Usable Catheter length	140 cm	Nominal Pressure	12 atm
Proximal Shaft:	Stainless steel AISI 304, low friction hypotube with Teflon coating	Rated Burst Pressure	22 atm [2.00 to 4.50mm]
Distal Shaft:	Mix Polyamide / PEBA with Hydrophilic coating	Average Burst Pressure	28 atm
Tip material / entry profile	0.017"		
Folds	3		

ORDERING INFORMATION

DIA	LENGTH				
2.00	08	10	12	15	20
2.50	08	10	12	15	20
2.75	08	10	12	15	20
3.00	08	10	12	15	20
3.50	08	10	12	15	20
4.00	08	10	12	15	20
4.50	08	10	12	15	20



Marketed by:
Zon Medical Devices
QUALITY AT ITS BEST.

The Netherland Office
4-15 EdelBox Osloweg
4 9723 BL Groningen
The Netherlands

Hyderabad Office

No. 2-3-125, Plot No. 36/B,
Second Floor, Road No. 8,
Co-operative Bank Colony,
Nagole, Hyderabad T.S.,
India 500 068.

Noida Office

5th Floor, B 522, Logix
Technova Block B,
Goutambudh Nagar, Noida
Expressway, Noida Sector
132 - 201304